



## Load Break Switch 3-pole 3 modules 63A

### Specification

RATED THERMAL CURRENT I <sub>THE</sub> (A)	80
BACK-UP FUSE (A)	80
RATED OPERATIONAL CURRENT AC21 IE (A)	400/415V = 80 A 500V = 80 A 690V = 80 A
RATED OPERATIONAL CURRENT AC22 IE (A)	400/415V = 63 A 500V = 63 A 690V = 63 A
RATED OPERATIONAL CURRENT AC23 IE (A)	400/415V = 40 A 500V = 40 A 690V = 40 A
RATED OPERATIONAL POWER AC-23 (KW)	400/415V = 22 kW 500V = 30 kW 690V = 37 kW
RATED SHORT-CIRCUIT CAPACITY (KA)	50
MECHANICAL ENDURANCE (NUMBER OF OPERATIONS)	50.000
TERMINALS / BOLT SIZE (MM <sup>2</sup> )	2,5 - 35
FASTENING TORQUE	2,5 Nm
MODULE WIDTH	3 modules (54mm)
STANDARDS	IEC 60 947-3, IEC 60 269-2, UL 508

## Variants

E-NUMBER	ARTICLE NO.	NUMBER OF POLES	RATED OPERATIONAL CURRENT AC-22	RATED OPERATIONAL CURRENT AC-23	PCS/PACK
2154460	KUE380	3	63A	40A	1/20