



PD4-CAS-GH DALI-2

Specification

SUPPLY VOLTAGE	230V AC $\pm 10\%$
POWER CONSUMPTION	approx. 0,4W
MATERIAL ENCLOSURE	Polycarbonate, UV-resistant
TEMPERATURE RANGE	-5°C...+45°C
INGRESS PROTECTION	IP54
PROTECTION CATEGORY	II
LIGHT VALUES	1 - 4000 Lux
AREA OF COVERAGE	circular 360°
RANGE OF COVERAGE	H 14m / T = 18°C: tangential r 22m / \varnothing 44m tangential r19m / \varnothing 30m
MOUNTING HEIGHT MIN./MAX./RECOMMENDED	5 m / 16 m / 14 m
RECOMMENDED HEIGHT FOR MOUNTING	14m
LIGHT MEASUREMENT	Mixed light, daylight + artificial light
MAX. NUMBERS OF CONNECTED EB	upp till 32
FOLLOW-UP TIME	1 sec - 60min
HALOGEN-FREE	Yes

Variants

E-NUMBER	ARTICLE NO.	DESCRIPTION	INGRESS PROTECTION	COLOUR	PCS/PACK
1301623	93471	PD4-CAS-GH DALI-2	IP54	White	1
1313683	92199	Skyddskorg BSK	-	White	1