



INDOOR-180-BMS-DALI-2

Specification

POWER CONSUMPTION	7 mA
MATERIAL ENCLOSURE	Polycarbonate, UV-resistant
TEMPERATURE RANGE	-25°C....+55°C
INGRESS PROTECTION	IP20
PROTECTION CATEGORY	II
AREA OF COVERAGE	180°
RANGE OF COVERAGE	T = 18°C: tangential max. r 10m radial max. r 3m
RECOMMENDED HEIGHT FOR MOUNTING	1,1m (max 2,2m)
LIGHT MEASUREMENT	Mixed light, daylight + artificial light
HALOGEN-FREE	Yes

Variants

E-NUMBER	ARTICLE NO.	DESCRIPTION	MOUNTING	INGRESS PROTECTION	COLOUR	PCS/PACK
1301467	93540	INDOOR-180-BMS-DALI-2 (insats)	INF Flush	IP20	-	1
1313640	92630	Täckram IP20	INF Flush	IP20	White RAL 9010	1
1300533	39241	Centrumplatta designkompatibel med Schneider Electric Exxact	-	-	White RAL 9003	1
1300594	39222	Centrumplatta designkompatibel med ELKO RS	-	-	White RAL 9010	1
1300534	39242	Centrumplatta designkompatibel med ABB Jussi	-	-	White RAL 9016	1
N4920138	92634	Täckram IP20	INF Flush	IP20	Antracit RAL 7021	1
N4920136	92632	Täckram IP20	INF Flush	IP20	1	
N4920137	92633	Täckram IP20	INF Flush	IP20	Silver RAL 9006	1
N4920135	92631	Täckram IP20	INF Flush	IP20	White RAL 9016	1
1313642	92141	Förhöjningsram utanpåliggande	UTP Surface	IP44	White RAL 9010	1
1313641	92139	Täckram IP54	INF Flush	IP54	White RAL 9010	1