



PD4N-BMS-DALI-2

Specification

| | |
|--|--|
| POWER CONSUMPTION | 7 mA |
| MATERIAL ENCLOSURE | Polycarbonate, UV-resistant |
| TEMPERATURE RANGE | -25°C....+55°C |
| PROTECTION CATEGORY | II |
| AREA OF COVERAGE | circular 360° |
| RANGE OF COVERAGE | Ø H 2.50m / T = 18°C: seated 6.40m tangential 24m radial 8m |
| RECOMMENDED HEIGHT FOR MOUNTING | 2,5m |
| LIGHT MEASUREMENT | Mixed light, daylight + artificial light |
| HALOGEN-FREE | Yes |

Variants

| E-NUMBER | ARTICLE NO. | DESCRIPTION | INGRESS PROTECTION | COLOUR | PCS/PACK |
|----------|-------------|--|--------------------|--------|----------|
| 1301465 | 93546 | PD4N-BMS-DALI2-TAK | IP20 | White | 1 |
| 1739249 | 93307 | PD2N- / PD4N-UP SM socle mounting set IP54 | IP54 | White | 1 |
| 1313683 | 92199 | Wire basket BSK | - | White | 1 |
| 1301325 | 93073 | Corridor lens PD4N type A | - | White | 1 |
| 1313699 | 93164 | Wall holder PD2N/PD4N | - | White | 1 |
| 1313711 | 93192 | SM socket for Wall holder | - | White | 1 |