



PD11-DALI LINK

Specification

MATERIAL ENCLOSURE	Polycarbonate, UV-resistant
TEMPERATURE RANGE	-25°C...+50°C
INGRESS PROTECTION	IP20
PROTECTION CATEGORY	II
SETTINGS	DALI LINK Bluetooth-app
LIGHT VALUES	10 - 2500 Lux
EXTENSION OF THE DETECTION AREA	with detector in slave mode
AREA OF COVERAGE	circular 360°
RANGE OF COVERAGE	\varnothing H 2.50m / T = 18°C: seated 3m tangential 9m radial 6m
RECOMMENDED HEIGHT FOR MOUNTING	2,5m
LIGHT MEASUREMENT	Mixed light, daylight + artificial light
FOLLOW-UP TIME	1 - 120min.
CHANNEL 1	For light control depending on brightness.
DIMENSIONS	H x \varnothing mm: TAK 48 x 52
VISIBLE PORTION WHEN BUILT INTO CEILING	H x \varnothing mm: 0,85 x 52

Variants

E-NUMBER	ARTICLE NO.	DESCRIPTION	INGRESS PROTECTION	COLOUR	PCS/PACK
1301098	93068	PD11-DALI LINK-FLAT	IP20	White	1
92537	IP20	Black	1		