



PD4-M-DACO-GH DALI-2

Specification

SUPPLY VOLTAGE	230 V / 50 Hz
POWER CONSUMPTION	approx. 2W
MATERIAL ENCLOSURE	Polycarbonate, UV-resistant
TEMPERATURE RANGE	-25°C...+50°C
PROTECTION CATEGORY	II
EXTENSION OF THE DETECTION AREA	with slave detector
AREA OF COVERAGE	circular 360°
RANGE OF COVERAGE	H 14m / T = 18°C: tangential r 22m / Ø 44m tangential r19m / Ø 30m
MOUNTING HEIGHT MIN./MAX./RECOMMENDED	5 m / 16 m / 14 m
RECOMMENDED HEIGHT FOR MOUNTING	14m
LIGHT MEASUREMENT	Mixed light, daylight + artificial light

For lightning control

DALI output:
80mA (guaranteed, 125mA (max.))

Follow-up time:
1 - 150min

Brightness set value:
10 - 2500 lux

CHANNEL 1

PUSH BUTTON

1 push button

HALOGEN-FREE

Yes

Variants

E-NUMBER	ARTICLE NO.	DESCRIPTION	INGRESS PROTECTION	COLOUR	PCS/PACK
1301606	93469	PD4-M-DACO-GH DALI-2	IP54	White	1
1301369	93067	BLE-IR-Adapter	-	Black	1
1301096	92846	Strömförsörjning PS-DALI	-	White	1
1313683	92199	Wire basket BSK	-	White	1