



## PD4N-M-DACO DALI-2

### Specification

SUPPLY VOLTAGE	230 V / 50 Hz
POWER CONSUMPTION	approx. 2W
MATERIAL ENCLOSURE	Polycarbonate, UV-resistant
TEMPERATURE RANGE	-25°C...+50°C
PROTECTION CATEGORY	II
EXTENSION OF THE DETECTION AREA	with slave detector
AREA OF COVERAGE	circular 360°
RANGE OF COVERAGE	<p>Ø H 2.50m / T = 18°C:                      seated 6.40m                      tangential 24m                      radial 8m</p>
RECOMMENDED HEIGHT FOR MOUNTING	2,5m
LIGHT MEASUREMENT	Mixed light, daylight + artificial light

For lightning control

DALI output:  
80mA (guaranteed, 125mA (max.))

Follow-up time:  
1 - 150min

Brightness set value:  
10 - 2500 lux

#### CHANNEL 1

PUSH BUTTON

1 push button

HALOGEN-FREE

Yes

## Variants

E-NUMBER	ARTICLE NO.	DESCRIPTION	INGRESS PROTECTION	COLOUR	PCS/PACK
1301609	93465	Förhöjningsram PD4N H	IP54	White	1
1301369	93067	BLE-IR-Adapter	-	Black	1
1313662	92094	Fjärrkontroll IR-PD-DALI	-	Grey	1
1301096	92846	Strömförsörjning PS-DALI	IP20	White	1
1301325	93073	Korridorlins PD4N Typ A	IP20	White	1
1313683	92199	Wire basket BSK	-	White	1
1301604	93460	PD4N-M-DACO DALI-2	IP20	White	1
1313699	93164	Wall holder PD2N/PD4N	-	White	1
1313711	93192	SM socket for Wall holder	-	White	1