



HF-H-MD1 Tak- och Väggh monterad HF-Teknik

Specification

SUPPLY VOLTAGE	230V AC $\pm 10\%$
POWER CONSUMPTION	approx. 0,8W
FREQUENCY	Radar / HF-technology: 5,8 GHz
MATERIAL ENCLOSURE	Polycarbonate, UV-resistant
TEMPERATURE RANGE	-35°C...+70°C
PROTECTION CATEGORY	II
SETTINGS	DIP switches
LIGHT VALUES	DIP switches 2 - 30 Lux
AREA OF COVERAGE	Ceiling mounted: 360° Wall mounted: 180°
RANGE OF COVERAGE	The range depends on the size and speed of the object Ceiling mounted: H 2.50m, \varnothing 1,6 - max. 16m Wall mounted: \varnothing 0,8 - max. 8m
RECOMMENDED HEIGHT FOR MOUNTING	Ceiling: 2,5m
FOLLOW-UP TIME	5sec - 25min
CHANNEL 1	For light control depending on brightness.
SWITCHING CAPACITY	1000 W, $\cos \varphi = 1$

DIMENSIONS 103 x 53 x 26mm

HALOGEN-FREE Yes

Variants

E-NUMBER	ARTICLE NO.	DESCRIPTION	COLOUR	PCS/PACK
-	94431	HF-H-MD1 Standard	White	1