



HF-MD1 Tak- och Väggh monterade HF-Teknik

Specification

SUPPLY VOLTAGE	230V AC $\pm 10\%$ / 50Hz
POWER CONSUMPTION	approx. 1,2W
FREQUENCY	Radar / HF-technology: 5,8 GHz
MATERIAL ENCLOSURE	Polycarbonate, UV-resistant
TEMPERATURE RANGE	-15°C....+50°C
PROTECTION CATEGORY	II
SETTINGS	Potentiometers and DIP switches
LIGHT VALUES	Potentiometer 2 - 2000 Lux
AREA OF COVERAGE	Ceiling mounted: 360° Wall mounted: 180°
RANGE OF COVERAGE	The range depends on the size and speed of the object Ceiling mounted: H 2.50m, \varnothing 0,4 - max. 16m Wall mounted: \varnothing 0,2 - max. 8m
RECOMMENDED HEIGHT FOR MOUNTING	Ceiling: 2,5m
FOLLOW-UP TIME	HF-MD1: 5sec - 15min HF-MD1 ESL: 5min - 15min
CHANNEL 1	For light control depending on brightness.
SWITCHING CAPACITY	1200 W, $\cos \phi = 1$

DIMENSIONS 101 x 42 x 42mm

HALOGEN-FREE Yes

Variants

E-NUMBER	ARTICLE NO.	DESCRIPTION	INGRESS PROTECTION	COLOUR	PCS/PACK
N4920170	94401	HF-MD1	IP20	White	1
-	94417	HF-MD1 ESL	IP20	White	1