



HF-MD2 HF-Teknik

Specification

SUPPLY VOLTAGE	230V AC $\pm 10\%$ / 50-60Hz
POWER CONSUMPTION	approx. 1,2W
FREQUENCY	Radar / HF-technology: 5,8 GHz
MATERIAL ENCLOSURE	Polycarbonate, UV-resistant
TEMPERATURE RANGE	-15°C...+50°C
PROTECTION CATEGORY	II
SETTINGS	Potentiometers and DIP switches
LIGHT VALUES	Potentiometer 2 - 2000 Lux
AREA OF COVERAGE	Ceiling mounted: 360° Wall mounted: 180°
RANGE OF COVERAGE	The range depends on the size and speed of the object Ceiling mounted: H 2.50m, \varnothing 0,4 - max. 16m Wall mounted: \varnothing 0,2 - max. 8m
RECOMMENDED HEIGHT FOR MOUNTING	Ceiling: 2,5m
FOLLOW-UP TIME	5sec - 15min
CHANNEL 1	For light control depending on brightness.
SWITCHING CAPACITY	1200 W, $\cos \varphi = 1$ max. inrush current I_p (20ms) = 120 A
DIMENSIONS	H x \varnothing mm: UTP 45 x 116,5

Variants

E-NUMBER	ARTICLE NO.	DESCRIPTION	MOUNTING	INGRESS PROTECTION	COLOUR	PCS/PACK
-	94402	HF-MD2-INF	UTP Surface	IP20	White	1
1313683	92199	Skyddskorg BSK	-	-	White	1