



## PD11-M-1C-FLAT Till/Från

### Specification

SUPPLY VOLTAGE	110-240VAC / 50-60Hz
POWER CONSUMPTION	approx. 0,3W
MATERIAL ENCLOSURE	Polycarbonate, UV-resistant
TEMPERATURE RANGE	-25°C....+50°C
PROTECTION CATEGORY	II
SETTINGS	Remote control
EXTENSION OF THE DETECTION AREA	with slave detector
AREA OF COVERAGE	circular 360°
RANGE OF COVERAGE	Ø H 2.50m / T = 18°C: seated 3m tangential 9m radial 6m
RECOMMENDED HEIGHT FOR MOUNTING	2,5m
LIGHT MEASUREMENT	Mixed light, daylight + artificial light

For lightning control, 1x  $\mu$ -contact  
NO contact with tungsten pre-make contact

Switching power:  
2300 W,  $\cos \varphi = 1$   
1150 VA,  $\cos \varphi = 0,5$   
300W LED  
max. inrush current  $I_p$  (20ms) = 165 A  
max. inrush current  $I_p$  (200  $\mu$ s) = 800 A

Follow up time:  
5 min - 30 min, Pulse

Switch-on threshold:  
20 - 2000 lux

**CHANNEL 1**

<b>DIMENSIONS</b>	H x $\varnothing$ mm: TAK 60 x 52
<b>VISIBLE PORTION WHEN BUILT INTO CEILING</b>	H x $\varnothing$ mm: 0,85 x 52
<b>PUSH BUTTON</b>	1 push button
<b>HALOGEN-FREE</b>	Yes

## Variants

E-NUMBER	ARTICLE NO.	MOUNTING	INGRESS PROTECTION	COLOUR	PCS/PACK	DESCRIPTION
1300356	92583	TAK False ceiling	IP20	White	1	
-	92537	Täckring PD11 $\varnothing$ 52mm svart	-	-	Black	1