



## PD4-M-1C-GH Till/Från 1-kanalig för höga höjder

### Specification

SUPPLY VOLTAGE	110-240VAC / 50-60Hz
POWER CONSUMPTION	approx. 0,8W
MATERIAL ENCLOSURE	Polycarbonate, UV-resistant
TEMPERATURE RANGE	-25°C...+50°C
PROTECTION CATEGORY	II
SETTINGS	Remote control
EXTENSION OF THE DETECTION AREA	with slave detector
AREA OF COVERAGE	circular 360°
RANGE OF COVERAGE	H 14m / T = 18°C: tangential r 22m / Ø 44m tangential r19m / Ø 30m
MOUNTING HEIGHT MIN./MAX./RECOMMENDED	5 m / 16 m / 14 m
RECOMMENDED HEIGHT FOR MOUNTING	14m
LIGHT MEASUREMENT	Mixed light, daylight + artificial light

For lightning control, potential-free, 1x  $\mu$ -contact  
NO contact with tungsten pre-make contact

Switching power:  
2300 W,  $\cos \varphi = 1$   
1150 VA,  $\cos \varphi = 0,5$   
300W LED

max. inrush current  $I_p$  (20ms) = 165 A  
max. inrush current  $I_p$  (200  $\mu$ s) = 800 A

Follow up time:  
15 sec - 30 min, Puls

Switch-on threshold:  
20 - 2000 lux

**CHANNEL 1**

<b>DIMENSIONS</b>	H x $\varnothing$ mm: UTP 63 x 98
<b>PUSH BUTTON</b>	1 push button
<b>HALOGEN-FREE</b>	Yes

## Variants

E-NUMBER	ARTICLE NO.	DESCRIPTION	MOUNTING	INGRESS PROTECTION	COLOUR	PCS/PACK
1313582	92245	PD4-M-GH-UTP	UTP Surface	IP20	White	1
1313683	92199	Skyddskorg BSK	-	-	White	1
1313675	92161	Förhöjningsram IP54	UTP Surface	IP54	White	1
1300172	92375	Förhöjningsram IP65 för PD4-UTP (IP20)	UTP Surface	IP65	White	1
1300191	92479	IR-PD-GH-LD Batterier är ej inkluderade (3st AAA)	-	-	Grey	1