



PD4-M-1C-K

Specification

SUPPLY VOLTAGE	110-240VAC / 50-60Hz
POWER CONSUMPTION	approx. 0,7W
MATERIAL ENCLOSURE	Polycarbonate, UV-resistant
TEMPERATURE RANGE	-25°C....+50°C
PROTECTION CATEGORY	II
SETTINGS	Potentiometers, DIP switches and remote control
EXTENSION OF THE DETECTION AREA	with slave detector
AREA OF COVERAGE	circular 360°
RANGE OF COVERAGE	Ø H 2.50m / T = 18°C: tangential 40m radial 20m
RECOMMENDED HEIGHT FOR MOUNTING	2,5m
LIGHT MEASUREMENT	Mixed light, daylight + artificial light

For lightning control, potential-free, 1x μ -contact
NO contact with tungsten pre-make contact

Switching power:
2300 W, $\cos \varphi = 1$
1150 VA, $\cos \varphi = 0,5$
300W LED
max. inrush current I_p (20ms) = 165 A
max. inrush current I_p (200 μ s) = 800 A

CHANNEL 1

Follow up time:
15 sec - 30 min, Puls

Switch-on threshold:
10 - 2000 lux

DIMENSIONS

H x \varnothing mm: UTP 73 x 101, TAK 103 x 97

VISIBLE PORTION WHEN BUILT INTO CEILING

H x \varnothing mm: 30 x 97

PUSH BUTTON

1 push button

HALOGEN-FREE

Yes

Variants

E-NUMBER	ARTICLE NO.	DESCRIPTION	MOUNTING	INGRESS PROTECTION	COLOUR	PCS/PACK
1300177	92587	PD4-M-1C-K-UTP	UTP Surface	IP54	White	1
1300178	92586	PD4-M-1C-K-TAK	TAK False ceiling	IP20	White	1
1313683	92199	Skyddskorg BSK	-	-	White	1
1300173	92376	Förhöjningsram IP65 för PD4-UTP (IP54)	UTP Surface	IP65	White	1
1300174	92520	IR-PD-1C	-	-	Grey	1
1313664	92159	IR-PD-MINI	-	-	Grey	1