



PD4-M-2C-DUO Till/Från 2-kanalig DUO

Specification

SUPPLY VOLTAGE	110-240VAC / 50-60Hz
POWER CONSUMPTION	approx. 0,5W
MATERIAL ENCLOSURE	Polycarbonate, UV-resistant
TEMPERATURE RANGE	-25°C...+50°C
PROTECTION CATEGORY	II
SETTINGS	Potentiometers, DIP switches and remote control
EXTENSION OF THE DETECTION AREA	with slave detector
AREA OF COVERAGE	circular 360°
RANGE OF COVERAGE	Ø H 2.50m / T = 18°C: seated 6.40m tangential 24m radial 8m
RECOMMENDED HEIGHT FOR MOUNTING	2,5m
LIGHT MEASUREMENT	Mixed light, daylight + artificial light

For lightning control, 1x μ -contact
NO contact with tungsten pre-make contact

Switching power:
2300 W, $\cos \varphi = 1$
1150 VA, $\cos \varphi = 0,5$
300W LED
max. inrush current I_p (20ms) = 165 A
max. inrush current I_p (200 μ s) = 800 A

CHANNEL 1

Follow up time:
1 min - 30 min

Switch-on threshold:
10 - 2000 lux

For lightning control, 1x μ -contact

Switching power:
2300 W, $\cos \varphi = 1$
1150 VA, $\cos \varphi = 0,5$
300W LED
max. startström I_p (20ms) = 165 A, I_p (200 μ s) = 800 A

CHANNEL 2

Follow up time:
1 min- 30 min

Switch-on threshold:
10 - 2000 lux

DIMENSIONS

H x \varnothing mm: UTP 68 x 117, TAK 103 x 97, INF 74 x 97

VISIBLE PORTION WHEN BUILT INTO CEILING

H x \varnothing mm: TAK 30 x 97, INF 30 x 97

PUSH BUTTON

2 push buttons

HALOGEN-FREE

Yes

Variants

E-NUMBER	ARTICLE NO.	DESCRIPTION	MOUNTING	INGRESS PROTECTION	COLOUR	PCS/PACK
1313576	92158	PD4-M2C-DUO-UTP	UTP Surface	IP54	White	1
1313588	92251	PD4-M2C-DUO-TAK	TAK False ceiling	IP20	White	1
1313597	92252	PD4-M2C-DUO-INF	INF Flush	IP20	White	1
1313683	92199	Skyddskorg BSK	-	-	White	1
1300173	92376	Förhöjningsram IP65 för PD4-UTP (IP54)	UTP Surface	IP65	White	1
1313661	92092	IR-PD-DUO	-	-	Grey	1